

# OCEAN53 PAINTS

## TECHNICAL DATASHEET

**Product Reference:** Grafo Decor  
**Date of Issue:** 01/06/2023



Page 1 of 2

**Product Name:** Grafo Decor  
**Manufacturer:** Ocean53paints  
New Industrial Area, Umm Dera,  
Umm Al Quwain, United Arab Emirates  
**Contact:** Info@ocean53paints.com

<b>Product Name</b>	Grafo Decor
<b>Description and Usage</b>	Grafo Decor is an emulsion based textured emulsion paint suitable for interior and exterior application. This product contains high quality marble chips it will cover minor surface imperfections and capable of hiding hairline cracks. Kodak Shield Grafo Decor is a tough weather resistant textured coating contains anti-fungal & anti-bacterial additives with excellent alkali resistance.
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Excellent resistance to tough atmospheric conditions</li><li>• Hides minor surface imperfections and hairline cracks</li><li>• Suitable for application on concrete, plaster, gypsum board and for wooden surface also</li></ul>
<b>Pack Size</b>	18 Litre
<b>Colour Range</b>	White and selected colour shades
<b>Film Properties:</b> <i>Water Resistance</i>	Resistant to the levels of atmospheric humidity normally experienced in interior & exterior environment. Not suitable for use on immersed surface.
<b>Composition (nominal)</b>	Binder: Acrylic Copolymer Solvent: Water
<b>Product Data:</b> <i>Finish</i> <i>Volume Solids %</i> <i>Typical WFT (microns) per coat</i> <i>Typical DFT (microns) per coat</i> <i>Theoretical Coverage</i>	Grooved Texture / Matt 69 ± 2% 1450 – 1650 µm 1000 – 1140 µm 0.7 – 0.6 m <sup>2</sup> /litre/coat

**Factory:**  
 New Industrial Area, Umm Dera,  
Umm Al Quwain, UAE  
 50 537 8649

**Office:**  
 Ras Al Khor, Ind 2  
 +971 50 537 8649

 Info@ocean53paints.com  
 www.ocean53paints.com

# OCEAN53 PAINTS

## TECHNICAL DATASHEET

**Product Reference:** Grafo Decor

**Date of Issue:** 01/06/2023

Page 2 of 2

**Product Name:** Grafo Decor

**Manufacturer:** Ocean53paints

New Industrial Area, Umm Dera,  
Umm Al Quwain, United Arab Emirates

**Contact:** Info@ocean53paints.com

<i>Practical Spreading Rate</i>	Depending on substrate, application method, application conditions and system, etc.			
<i>Specific Gravity</i>	White 1.90 ± 0.05 kg/l			
<i>Drying/Overcoating Information</i>	°C	Touch Dry	Overcoating	Hard Dry
	@ 30°C	1 - 2 hrs	6 - 8 hrs	24 hrs
<i>Application</i>	Trowel			
<b>Thinning:</b>	<i>Trowel</i>	Ready for use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 parts of paint (10%).		
<b>Cleaning Up</b>	Clean all equipment with water immediately after use.			
<b>Surface Preparation</b>	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi and algae with appropriate fungi and algae remover. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.			
<b>System Information:</b>				
<i>New, Normal, Sound Surfaces</i>	Sealer (1 Coat)		Top Coat (If required)	
	Acrylic Primer			
			Ocean53 Exterior Topcoat Range	
	Grafio Decor			
<b>HSE Information</b>	Product Safety Data Sheet available upon request.			

**Factory:**

New Industrial Area, Umm Dera,  
Umm Al Quwain, UAE

50 537 8649

**Office:**

Ras Al Khor, Ind 2

+971 50 537 8649

Info@ocean53paints.com

www.ocean53paints.com