

TECHNICAL DATASHEET

Product Reference: Pearl Eggshell Emulsion
Date of Issue: 01/06/2023

Page 1 of 2

Product Name: Pearl Eggshell Emulsion
Manufacturer: Ocean 53 Paints
 New Industrial Area, Umm Dera,
 Umm Al Quwain, United Arab Emirates
Contact: Info@ocean53paints.com

Product Name	Pearl Eggshell Emulsion
Description and Usage	Pearl Eggshell Emulsion is a premium highly washable interior/exterior emulsion paint based on acrylic copolymer. This hard-wearing product has low VOC which ensures good indoor/outdoor air quality.
Benefits	<ul style="list-style-type: none"> • This product is highly washable and resists stains • Easy and fast application • High hiding and exhibit good weather resistance • This product has inherent anti-chalking properties • Free from harmful chemicals like APEO, formaldehyde and heavy metals etc.
Pack Size	18 Litre, 3.6 Litre
Colour Range	White and selected colour shades
Film Properties: <i>Water Resistance</i>	Resistant to the levels of atmospheric humidity normally experienced in interior/exterior environment. Not suitable for use on immersed surfaces.
Composition (nominal)	Binder: Acrylic Copolymer Solvent: Water
Product Data: <i>Finish</i> <i>Volume Solids %</i> <i>Typical WFT (microns) per coat</i> <i>Typical DFT (microns) per coat</i> <i>Theoretical Coverage</i> <i>Practical Spreading Rate</i>	Smooth/Eggshell 40 ± 2% 75 – 100 µm 30 – 40 µm 13.33 – 10.0 m ² /litre/coat Depending on substrate, application method, application conditions and system, etc.

TECHNICAL DATASHEET

Product Reference: Pearl Eggshell Emulsion

Date of Issue: 01/06/2023

Page 2 of 2

Product Name: Pearl Eggshell Emulsion

Manufacturer: Ocean 53 Paints
New Industrial Area, Umm Dera,
Umm Al Quwain, United Arab Emirates

Contact: Info@ocean53paints.com

<div>Specific Gravity</div> <div>Drying/Overcoating Information</div> <div>Application</div>	White 1.25 ± 0.05 kg/l			
	°C	Touch Dry	Overcoating	Hard Dry
	@ 30°C	20 - 30 min	1 - 2 hrs	4 - 6 hrs
	Brush, Roller			
<div>Thinning:</div> <div>Brush, Roller</div>	Add up to 5-10% of fresh water depend on the method of application and site conditions.			
Cleaning Up	Clean all equipment with water immediately after use.			
Surface Preparation	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi and algae with appropriate fungi and algae remover. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.			
<div>System Information:</div> <div>New, Normal, Sound Surfaces</div>	Sealer (1 Coat)		Finish (2 Coats)	
	PVA Primer			
			Pearl Eggshell Emulsion	
	Stucco Filler(1 or 2 coats)			
Health, Safety and Environment Information	Product Safety Data Sheet available upon request.			

Factory:

 New Industrial Area, Umm Dera,
Umm Al Quwain, UAE
 +971 50 537 8649

Office:

 Ras Al Khor, Ind 2
 +971 50 537 8649

 Info@ocean53paints.com

 www.ocean53paints.com